CLAIMS

1.	A method for call diversion in a communications system with a plurality of terminals which are connected to a local area network, the method comprising the steps of:

5	activating a call diversion from a first terminal to a second terminal;

transmitting information relating to the activated call diversion to an agent unit; and

diverting a call for the first terminal using the transmitted information.

10	2.	A method for call diversion in a communications system as claimed in Claim 1, wherein an H.323 protocol is used in the communications system.

3.	A method for call diversion in a communications system as claimed in Claim 1, wherein the agent unit is a third terminal of the communications system.

15

4.	A method for call diversion in a communications system as claimed in Claim 1, wherein the first terminal can be disabled.

5.	A method for call diversion in a communications system as claimed in 20	Claim 1, wherein information is transmitted to the agent unit in a protocol layer above an H.323 protocol.

6.	A method for call diversion in a communications system as claimed in Claim 5, wherein the agent unit stores a list of the plurality of terminals connected to 25	the local area network.

7.	A method for call diversion in a communications system as claimed in Claim 6, wherein the agent unit controls the call diversion.

30	8.	A computer-controlled device in a communications system, comprising:

a plurality of terminals connected to a local area network; and

7

an agent unit for managing call diversions of the terminals.

9.   A computer-controlled device in a communications system as claimed in Claim 8, wherein a call diversion is activated from a first terminal to a second terminal, information is transmitted relating to the activated call diversion to the agent unit, and a call is diverted for the first terminal using the transmitted information.